



NETWORKING & TELECOMMUNICATIONS END-TO-END SOLUTIONS

FIBRE OPTIC CABLE

WATERPROOF CABLE

PRE-TERM BREAKOUT

PRODUCT SPECIFICATIONS

Linxcom's Fibre Optic waterproof cable are widely used in data transmission network.

They are manufactured with strong jacket and waterproof sealed.

OUTER JACKET CORRUGATED STEEL TAPE SUB-CABLE ARAMID YARN STRENGTH MEMBER TIGHT BUFFER **OPTICAL FIBRE**

APPLICATIONS

- Horizontal wiring in LAN
- Data communication
- **Outdoor Application**

FEATURES BENEFITS

- 4-24 Core
- Flame Retardant
- Waterproof
- Durable and High Quality

JACKET SPECIFICATIONS	
Material	LSZH
Colour	Black
Outer Diameter	1.5±0.2mm
Rip Cord	
Tensile Strength	Short 1000 Long 500
Crush Resistance	300 N/10cm 1000 N/10cm
Bending Radius	Dynamic 20D Static 10D

CONSTRUCTION SPECIFICATIONS		
Fibre Count	2-4	
Sub Unit Diameter	3.0±0.1mm	
Strength Member Diameter	1.0mm	
Approx. Cable Weight	110 kg/km	
Strength Member	Steel Wire	

ENVIRONMENTAL SPECIFICATIONS		
Operation (°C)	-20~+70	
Installation (°C)	-20~+70	

ORDERING INFORMATION

Part Number

P4FCAFOS2BOW20 Preterm 4C FC/APC Fan-Out OS2 Breakout Waterproof 20m LSZH