



## FIBRE MANAGEMENT

# DOME ENCLOSURE

# DER03

### PRODUCT SPECIFICATIONS

Linxcom model DER03 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

### APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Pipeline Mounting



### FEATURES

- HQ Polypropylene
- Up to 96F
- Adjustable Cassettes

### BENEFITS

- Sturdy IP 68 & IK 10
- No Special Tools Required
- Protects Fibres in Field



Up to 96  
Fibres



IP68  
Rated



Pole  
Mountable



Wall  
Mountable



Direct  
Buriable

### SPECIFICATIONS

|                       |   |
|-----------------------|---|
| Purpose               | Aerial, Direct-Burial, Wall & Pipeline Mounting |
| Capacity              | 96  |
| Cable Entries         | 9   |
| Dimensions (mm)       | 470x210   |
| Weight (kg)           | 2.0   |
| Sealing               | Heat Shrink                                     |
| Material              | Polypropylene                                   |
| Splicing Per Cassette | 12,24   |
| Cable Diameter (mm)   | φ8~20   |

### ENVIRONMENTAL SPECIFICATIONS

|                   |         |
|-------------------|---------|
| Operation (°C)    | -40~+65 |
| Installation (°C) | -40~+65 |



### ORDERING INFORMATION

| Product Code | Model | Seal        | Cable Entries | Core Size/Capacity      |
|--------------|-------|-------------|---------------|-------------------------|
| LXMDER03BXXH | DER03 | Heat Shrink | 9             | 12,24,36,48,60,72,84,96 |