



## FIBRE MANAGEMENT

# DOME ENCLOSURE

# DER08

## PRODUCT SPECIFICATIONS

Linxcom model DER08 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

## APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Pipeline Mounting



## FEATURES

- HQ Polypropylene
- Up to 120F
- Adjustable Cassettes

## BENEFITS

- Sturdy IP 68 & IK 10
- No Special Tools Required
- Protects Fibres in Field



## SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	120
Cable Entries	5
Dimensions (mm)	470x210
Weight (kg)	4.3-4.8
Sealing	Mechanical
Material	Polypropylene
Splicing Per Cassette	24
Cable Diameter (mm)	φ08~17.5

## ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65

## ORDERING INFORMATION

Product Code	Model	Seal	Cable Entries	Core Size/Capacity
LXMDER08BXXM	DER08	Mechanical	5	12,24,36,48,60,72,84,96,108,120

