



## FIBRE MANAGEMENT

# DOME ENCLOSURE

# DER09

### PRODUCT SPECIFICATIONS

Linxcom model DER09 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

### APPLICATIONS


- Aerial
- Direct- Burial
- Wall & Pipeline Mounting

### FEATURES

- HQ Polypropylene
- Up to 144F
- Adjustable Cassettes

### BENEFITS

- Sturdy IP 68 & IK 10
- No Special Tools Required
- Protects Fibres in Field



### SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	144
Cable Entries	5
Dimensions (mm)	450x230
Weight (kg)	4.2-4.8
Sealing	Mechanical
Material	Polypropylene
Splicing Per Cassette	24
Cable Diameter (mm)	φ08~17.5

### ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65



### ORDERING INFORMATION

Product Code	Model	Seal	Cable Entries	Core Size/Capacity
LXMDER09BXXM	DER09	Mechanical	5	12,24,36,48,60,72,84,96,108,120,132,144