



## FIBRE MANAGEMENT

# DOME ENCLOSURE

# DER13B

### PRODUCT SPECIFICATIONS

Linxcom model DER13B Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

### APPLICATIONS



- Aerial
- Direct- Burial
- Wall & Pipeline Mounting

### FEATURES

- HQ Polypropylene
- Up to 144F
- Adjustable Cassettes

### BENEFITS

- Sturdy IP 68 & IK 10
- No Special Tools Required
- Protects Fibres in Field



### SPECIFICATIONS

<b>Purpose</b>	Aerial, Direct-Burial, Wall & Pipeline Mounting
<b>Capacity</b>	144
<b>Cable Entries</b>	17
<b>Dimensions (mm)</b>	400xφ270
<b>Weight (kg)</b>	4.5-5.0
<b>Sealing</b>	Heat Shrink
<b>Material</b>	Polypropylene
<b>Splicing Per Cassette</b>	6 or 12
<b>Cable Diameter (mm)</b>	φ8~25.0

### ENVIRONMENTAL SPECIFICATIONS

<b>Operation (°C)</b>	-40~+65
<b>Installation (°C)</b>	-40~+65



### ORDERING INFORMATION

Product Code	Model	Seal	Cable Entries	Core Size/Capacity
LXMDER13BBXXH	DER13B	Heat Shrink	17	6,12,24,36,48,60,72,84,96,108,120,132,144