



FIBRE MANAGEMENT

DOME ENCLOSURE

DER15

PRODUCT SPECIFICATIONS

Linxcom model DER15 Dome Enclosure provides protection over direct, branch and terminal connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Pipeline Mounting

FEATURES

- HQ Polypropylene
- Up to 96F
- Adjustable Cassettes

BENEFITS

- Sturdy IP 68 & IK 10
- No Special Tools Required
- Protects Fibres in Field



Up to 96 Fibres



IP68 Rated



Pole Mountable



Wall Mountable



Direct Buriable

SPECIFICATIONS

Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting
Capacity	96
Cable Entries	4
Dimensions	190x440mm
Weight (kg)	2.3-2.6
Sealing	Heat Shrink
Material	Polypropylene
Splicing Per Cassette	12
Cable Diameter(mm)	φ25

ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+65
Installation (°C)	-40~+65



ORDERING INFORMATION

Product Code	Model	Seal	Cable Entries	Core Size/Capacity
LXMDER15BXXH	DER15	Heat Shrink	4	12,24,36,48,60,72,84,96