POLISHING FILMS

DIAMOND

PRODUCT SPECIFICATIONS

Polishing Films are used in fibre optic termination processes to polish and prepare connector ferrules for use.

We offer coarse to fine polishing films for each step of the polishing process and to allow a high quality finish for optimised fibre optic network performance.

TECHNICAL SPECIFICATIONS								
Granularity (um)	0.1	0.2	0.5	1	3	6	9	15
Colour	Light Brown	Grey	Brown/Yellow	Lavender	Pink	Yellow	Blue	Tawny
Available Sizes (mm)	Round: φ70, φ110, φ127, φ203 Square: 114x114, 152x152, 228x228 Ribbon: 1.6, 2.0, 2.5, 3.0, 3.2, 3.8, 5.0, 12.6, 25.4							

POLISHING FILMS
DIAMOND

ORDERING INFORMATION

Film Type	Diamond	**D**
Granularity	0.1um	**0.1UM**
	0.2um	**0.2UM**
	0.5um	**0.5UM**
	1um	**1UM**
	3um	**3UM**
	6um	**6UM**
	9um	**9UM**
	15um	**15UM**
Size	Round 70mm	**RD70**
	Round 110mm	**RD110**
	Round 127mm	**RD127**
	Round 203mm	**RD203**
	Square 114mm	**SQ114**
	Square 152mm	**SQ152**
	Square 228mm	**SQ228**
	Ribbon 1.6mm	**R1.6**
	Ribbon 2.0mm	**R2.0**
	Ribbon 2.5mm	**R2.5**
	Ribbon 3.0mm	**R3.0**
	Ribbon 3.2mm	**R3.2**
	Ribbon 3.8mm	**R3.8**
	Ribbon 5mm	**R5.0**
	Ribbon 12.6mm	**R12.6**
	Ribbon 25.4mm	**R25.4**
Colour	Light Brown	**LB**
	Grey	**GR**
	Brown/Yellow	**B/Y**
	Lavender	**LAV**
	Pink	**PK**
	Yellow	**YEL**
	Blue	**BL**
	Tawny	**TAW**

Example: **D0.1UMRD70LB**- Diamond Polishing Film 0.1um Round 70mm Light Brown