




FIBRE OPTIC CABLE

DUCT CABLE

NON ARMoured

PRODUCT SPECIFICATIONS

Linxcom Outdoor Duct Cable features a non-armoured single loose tube design with an FRP as its central member. The high strength loose tube is hydrolysis resistant while the tube filling compound ensure a critical protection of the fibre. This cable is suitable for aerial and duct installation.



APPLICATIONS

- Aerial
- Direct
- Duct

FEATURES

- 12-288 Core
- Strength Member

BENEFITS

- CST FRP
- Water blocking ensures reliable waterproofing



JACKET SPECIFICATIONS

Material	PE
Colour	Black
Outer Diameter	12.0±0.5mm
Rip Cord	--
Tensile Strength	1500N Short Term 600N Long Term
Crush Resistance	1000N/100 Short Term 300N/100 Long Term

CONSTRUCTION SPECIFICATIONS

Fibre Count	96
Fibre Type	
Weight (kg)	100/km
Strength Member	FRP

ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40 ~+60
Installation (°C)	-40 ~+60

ORDERING INFORMATION

Part Number	Construction	Fibre Type	Jacket
SLTNAD	12,24,48,72,96,120,144,168,192,216,240,264,288	G652D, G655C, G655D, OM1, OM2, OM3, OM4, OM5	PVC LSZH PE