





FIBRE MANAGEMENT

INLINE ENCLOSURE

PP01

PRODUCT SPECIFICATIONS

Linxcom model PP01- Inline Enclosure provides protection over direct, branch and continual connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- **Direct-Burial**
- Wall & Pipeline Mounting

FEATURES

BENEFITS

- HQ Polypropylene
- Up to 96F
- Removable Adaptor Plate
- Sturdy IP 68 & IK 10
 - No Special Tools
 - Required
- Protects Fibres in Field















SPECIFICATIONS				
Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting			
Capacity	96			
Cable Entries	4			
Dimensions (mm)	432 x 186 x 100			
Weight (kg)	3.8-4.2			
Sealing	Mechanical			
Material	Polypropylene			
Splicing Per Cassette	24			
Cable Diameter (mm)	φ10~21			
ENVIRONMENTAL SPECIFICATIONS				

-40~+65

-40~+65



ORDERING INFOR	RMATION
D 1 10 1	

Operation (°C)

Installation (°C)

Product Code	Model	Seal	Cable Entries	Core Size/Capacity
LXMPP01INLXXM	PP01	Mechanical	4	24,48,72,96