



NETWORKING & TELECOMMUNICATIONS END-TO-END SOLUTIONS

PP07

FIBRE MANAGEMENT

INLINE ENCLOSURE

PRODUCT SPECIFICATIONS

Linxcom model PP07- Inline Enclosure provides protection over direct, branch and continual connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

APPLICATIONS

- Aerial
- Direct- Burial
- Wall & Pipeline Mounting

FEATURES

BENEFITS

- HQ PolypropyleneUp to 96F
- Sturdy IP 68 & IK 10
- No Sp
- Removable Adaptor Plate
- No Special Tools Required Protects Fibres in Field
- Up to 96 Fibres Rated Pole Wall Direct Buriable

SPECIFICATIONS				
Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting			
Capacity	96			
Cable Entries	4			
Dimensions (mm)	455x180x120			
Weight (kg)	2.2-2.8			
Sealing	Mechanical			
Material	Polypropylene			
Splicing Per Cassette	12,24			
Cable Diameter (mm)	φ10~21			
ENVIRONMENTAL SPECIFICATIONS				
ENVIRONMENTAL SPECIF	ICATIONS			
Operation (°C)	-40~+65			
Installation (°C)	-40~+65			



ORDERING INFORMATION					
Product Code	Model	Seal	Cable Entries	Core Size/Capacity	
LXMPP07INLXXM	PP07	Mechanical	4	12,24,36,48,60,72,84,96	



