



NETWORKING & TELECOMMUNICATIONS END-TO-END SOLUTIONS

**PP09** 

FIBRE MANAGEMENT

# **INLINE ENCLOSURE**

## **PRODUCT SPECIFICATIONS**

Linxcom model PP09- Inline Enclosure provides protection over direct, branch and continual connection for cables. They are easy and reliable to install, delivering high mechanical strength against every environmental condition. Widely used in many applications.

## **APPLICATIONS**

- Aerial
- Direct- Burial
- Wall & Pipeline Mounting

#### **FEATURES**

Plate

### BENEFITS


HQ Polypropylene Up to 120F

**Removable Adaptor** 

- Sturdy IP 68 & IK 10
- No Special Tools Required
- Protects Fibres in Field

SPECIFICATIONS				
Purpose	Aerial, Direct-Burial, Wall & Pipeline Mounting			
Capacity	120			
Cable Entries	8			
Dimensions (mm)	470x240x120			
Weight (kg)	3.6			
Sealing	Mechanical			
Material	Polypropylene			
Splicing Per Cassette	12,24			
Cable Diameter (mm)	<b>ф~</b>			
ENVIRONMENTAL SPECIFICATIONS				
Operation (°C)	-40~+65			
Installation (°C)	-40~+65			







ORDERING INFORMATION					
Product Code	Model	Seal	Cable Entries	Core Size/Capacity	
LXMPP09INLXXM	PP09	Mechanical	8	12,24,36,48,60,72,84,96,108,120	

WWW.LINX-COM.COM

SALES@LINX-COM.COM