



FIBRE OPTIC TOOLS & TEST EQUIPMENT

POLISHING FILMS

SILICA OXIDE

PRODUCT SPECIFICATIONS

Polishing Films are used in fibre optic termination processes to polish and prepare connector ferrules for use.

We offer coarse to fine polishing films for each step of the polishing process and to allow a high quality finish for optimised fibre optic network performance.



TECHNICAL SPECIFICATIONS

Granularity (um)	0.01	0.02
Colour	Transparent	Transparent
Available Sizes (mm)	Round: $\phi 70$, $\phi 110$, $\phi 127$, $\phi 203$ Square: 114x114, 152x152, 228x228 Ribbon: 1.6, 2.0, 2.5, 3.0, 3.2, 3.8, 5.0, 12.6, 25.4	



FIBRE OPTIC TOOLS & TEST EQUIPMENT

POLISHING FILMS

SILICA OXIDE

ORDERING INFORMATION

Film Type	Silica Oxide	SO
Granularity	0.01um 0.02um	0.01UM 0.02UM
Size	Round 70mm Round 110mm Round 127mm Round 203mm Square 114mm Square 152mm Square 228mm Ribbon 1.6mm Ribbon 2.0mm Ribbon 2.5mm Ribbon 3.0mm Ribbon 3.2mm Ribbon 3.8mm Ribbon 5mm Ribbon 12.6mm Ribbon 25.4mm	RD70 RD110 RD127 RD203 SQ114 SQ152 SQ228 R1.6 R2.0 R2.5 R3.0 R3.2 R3.8 R5.0 R12.6 R25.4
Colour	Transparent	TR

Example: **SO0.1UMRD70TR**- Silica Oxide Polishing Film 0.01um Round 70mm Transparent