



Networking & Telecommunications End-to End Solutions

Copper Structured Cabling

## Category 6<sub>A</sub> STP Keystone Jack





Linxcom CAT6<sub>A</sub> STP Keystone jacks comply with the EIA/TIA standard for Category 6 Augmented and are available in a choice of 90°, 180° shuttered and non-shuttered.

Available in Black, White or combination, all Linxcom keystone jacks come with covers and are individually tested and checked before they leave our factory.

#### **Features & Benefits**

- 3P Certified
- High temperature thermoplastic housing
- Compact design, 8 positions and 8 conductors
- Meets or exceed the requirement proposed by TIA /EIA
  568 B .2 and TIA/EIA Category 6<sub>A</sub>
- Phosphor Bronze contact with 6-50um gold plating
- Available in UTP or STP
- Low attenuation loss, high return loss
- Accepts 22-26 AWG solid wires with insulation diameter of 0.4-0.6mm

#### **Applications**

- POTS, T1&Tq fractional
- ASDN basic & primary rate
- 4/16 Mbps Token Ring (IEEE802.5)
- 10 BASE-T (IEEE802.3)
- 100 Mbps TP-PMD
- 10 Gbps Ethernet

- 52/155 Mbps ATM (ATM Forum)
- 100 BASE-T4 (Fast Ethernet)
- 100 VG-Any LAN (IEEE802.12)
- 100 BASE-T (Fast Ethernet)
- 1 Gbps Ethernet (IEEE802.3)

#### Colouring

Pair 1	Pair 2	Pair 3	Pair 4
Blue, Blue/White	Orange, Orange/White	Green, Green/White	Brown, Brown/White

#### **Product Images**









Networking & Telecommunications End-to End Solutions

### **Copper Structured Cabling**

# Category 6<sub>A</sub> STP Keystone Jack



#### **Performance**

Insertion Life	750 cycles minimum
IDC Life	200 times (22-26 AWG solid wire) minimum
Contact Material	Phosphor Bronze, Gold Plating (0.5mm)
IDC Material	Phosphor Bronze stamp pin (0.35mm)
Housing Material	PC UL94V-0
Conformance	EIA/TIA 568A/B wiring standards, ISO/IEC 11801:2002, EIA/TIA 568B.2.1:2002, RoHS

### **Ordering Information**

Using the available configurations amend/create a part number using the formula below.

Construction			Jack Type	
STP (Shielded Twisted Pair) STP		180° Keystone Jack KSJ		
STF	)	6A	KSJ	SLV
011		0/1	1100	OL V
Catagony		Colour		
Category		Colour		
Category 6 <sub>A</sub> (CAT6 <sub>A</sub> ) <b>6A</b>		Silver <b>SLV</b>		

Example: STP6AKSJSLV - Category 6A Shielded Twisted Pair 180° Keystone Jack - Silver

For any queries, please contact the Linxcom team using the details below.