



Voice

Category 3 UTP 25 Port Patch Panel

Linxcom UTP Voice (CAT3) patch panels are 19 inch rack mountable IDC/PCB moulded jack patch panels.

All panels comply with the EIA/TIA standard for Category 3 and are available in 25 port density.

Every patch panel is made with high quality materials and tested before packing.



Features & Benefits

- Space-saving high density 1U
- Meets or exceeds the requirement proposed by TIA /EIA 568 B .2 ,ISO/IEC 11801 Category 3
- Black electrostatic powder-coated corrosion-resistant steel
- 25 port Voice Patch Panel
- Sturdy aluminium plate around jacks
- Termination accepts 22, 23, 24 and 26 AWG (0.64-0.4) solid wires
- Easy wiring installation, fit for 110 punch-down tools
- Phosphor Bronze, 6-50 micro inches gold plated

Mechanical Characteristics

Insertion Life	750 cycles minimum
IDC Life	200 times (22-26 AWG solid wire) minimum
Plug/Jack Contact Force	100g minimum using FCC-approved plug
Insulation Resistance	100Mohms minimum
Contact Resistance	7Mohms maximum
Dielectricity Intensity	AC 1000Vrms, 50Hz or 60Hz in 60s
Plating	Silver/Gold
Plating Thickness	1.25um, 5um/ 3u", 6u", 15u", 30u", 50u"

Ordering Information

Product Code	Description
CAT3PP25	CAT3 25 Port Voice Patch Panel