



## Fibre Management

# Fibre Optic Outdoor Wall Box Single Door



Linxcom Fibre Optic Wall Boxes are designed to apply in the patching and splicing of outdoor fibre communication links, available for the connection of optical cable and optical splitters. IP65 Rated, to withstand harsh conditions, UV and rainfall resistant.

### Features & Benefits

- Made from high quality materials with a cold-rolled steel chassis
- Complete fibre management and accessories
- Houses splices, cassettes, pigtails, patch cords, splitters, media converters and adapters
- Various cable entries with rubber seals
- Ranging from 12-96 core sizes
- Single or double doors with rubber seals and locks
- IP65 Rated



Up to 192  
Fibres



IP65  
Rated



Wall  
Mountable

### Technical Specifications

Material	Cold-rolled Steel
Ports (SC or FC/ST Simplex)	12-96 (6-48x SC Duplex)
Cable Entries	8 (2x PG21 - 13-18mm Ø, 6x PG13.5 - 6-12mm Ø)
Dimensions (mm)	560 * 480 * 190
Weight (kg)	11.7
Accessories	Cable Glands & Seals, Cable Ties, Cable Grips, Splice Cassettes, Splice Protection Sleeves, Wall Fixings, Fibre Tubing, FM Blocks
IP Rating	65

### Ordering Information

Using the available configurations amend/create product codes using the formula below.

Box Type	Fibre Type	Simplex / Duplex / Quad
Outdoor Wall Box <b>OWB</b>	Unloaded <b>EM</b> Singlemode Loaded <b>SM</b> Multimode Loaded <b>MM</b> APC Loaded <b>SMA</b>	Simplex <b>S</b> Duplex <b>D</b> Quad (LC Only) <b>Q</b>

<b>OWB</b>	<b>S</b>	<b>EM</b>	<b>SC</b>	<b>S</b>	<b>48</b>
------------	----------	-----------	-----------	----------	-----------

Door Type	Adapter Type	Port Density
Single Door <b>S</b>	FC <b>FC</b> ST <b>ST</b> SC <b>SC</b> LC <b>LC</b>	12 <b>12</b> 24 <b>24</b> 48 <b>48</b> 96 <b>96</b>

(Not for SC Duplex)

Example: **OWBSEMSCS48** - Unloaded SC Simplex 48 Port Single Door Outdoor Wall Box