





Fibre Management

Outdoor Terminal Box – Model 10



Linxcom Fibre Optic Terminal Boxes are light and compact whilst maintaining adequate fibre storage needs and minimum bend radius. It is especially suited for connecting and protection for fibre cable of FTTx

It can hold 24 SC simplex ports.



Technical Specifications

Material	Plastic
Ports (SC or FC/ST Simplex)	24
Cable Entries	26 (2 entry 24 exit)
Cable Entry Diameter Range (mm)	15 Ø max
Dimensions (mm)	330 * 225 * 90
Weight (kg)	2
IP Rating	65
Humidity	93% at 40°C
Temperature (°C)	-40 ~ 60

Features

- It is suitable for wall-mounting installation
- It is IP65
- It is suitable for SC adapter's installation and usage
- It is easily to access the box with hinged lid
- It is applicable for outdoor cables or indoor soft cables
- The maximum capacity is 12 fibres.

Ordering Information

Using the available configurations amend/create product codes using the formula below.

Box Type		Fibre Type		Simplex / Duplex / Quad	
Outdoor Terminal Box	OTB	Unloaded	EM	Simplex	S
		Singlemode Loaded	SM		
		Multimode Loaded	MM		
		Singlemode APC Loaded	SMA		
OTB	10	EM	SC	S	24
Model		Adapter Type		Port Density	
Model 10	10	SC	SC	24 Ports	24

Example: **OTB10EMSCS24** - Unloaded SC Simplex 24 Port Outdoor Outdoor Terminal Box Model 10

For any queries, please contact the Linxcom team using the details below.