




Fibre Management

Outdoor Terminal Box – Model 7



Lincom Fibre Optic Terminal Boxes are light and compact whilst maintaining adequate fibre storage needs and minimum bend radius.


This model can hold up to 48 SC Simplex or 48 LC duplex ports.



Up to 48
Fibres



IP65
Rated



Wall
Mountable

Technical Specifications

Material	Plastic
Ports (SC or FC/ST Simplex)	48
Cable Entries	2 entry 48 exit and 1 knockout
Dimensions (mm)	380 * 350 * 140
Weight (kg)	2.1
Accessories	Cable Ties, Wall Fixings (<i>More Accessories Available</i>)
IP Rating	65
Operating Temperature	-5°C +40°C
Relative Humidity	≤ 90% (+30°C)
Atmospheric Pressure	70Kpa – 106Kpa
Storage Temperature	-40°C + 70°C



Fibre Management

Outdoor Terminal Box – Model 7

Ordering Information

Using the available configurations amend/create product codes using the formula below.

Box Type		Fibre Type		Simplex / Duplex / Quad	
Outdoor Terminal Box	OTB	Unloaded Singlemode	EM	Simplex	S
		Multimode Loaded	SM	Duplex (<i>LC Only</i>)	D
		Singlemode APC Loaded	MM		
			SMA		
OTB	7	EM	SC	D	24
Model		Adapter Type		Port Density	
Model 7	7	SC	SC	24 Ports	24
		LC	LC	36 Ports	36
		LC Quad	LC	48 Ports	48

Example: **OTB7EMSCD24** - Unloaded SC Duplex 24 Port Outdoor FTTH Terminal Box Model 7

For any queries, please contact the Linxcom team using the details below.