




## Fibre Management

# Outdoor Terminal Box – Model 9



Linxcom Fibre Optic Terminal Boxes are light and compact whilst maintaining adequate fibre storage needs and minimum bend radius. It is especially suited for connecting and protection for fibre cable of FTTx


It can hold 12 SC simplex ports or 24 LC duplex



Up to 60  
Fibres



IP65  
Rated



Wall  
Mountable

### Technical Specifications

Dimension (mm)	300 x 265 x 78
Cable Ports	Max 6
Number of the tray	Max 5
Splice capacity of each tray	6f single layer 12f double layer
Number of the adapters	Max 24/SC SX
Weight (kg)	1.22

### Features

- It is suitable for wall-mounting installation
- It is IP65
- It is suitable for SC adapter's installation and usage
- It is easily to access the box with hinged lid
- It is applicable for outdoor cables or indoor soft cables
- The maximum capacity is 60 fibres.

### Ordering Information

Using the available configurations amend/create product codes using the formula below.

Box Type		Fibre Type			Simplex / Duplex / Quad	
Outdoor Terminal Box	<b>OTB</b>	Unloaded	<b>EM</b>	Simplex	<b>S</b>	
		Singlemode Loaded	<b>SM</b>	Duplex (LC only)	<b>D</b>	
		Multimode Loaded	<b>MM</b>			
		Singlemode APC Loaded	<b>SMA</b>			
<b>OTB</b>	<b>09</b>	<b>EM</b>	<b>SC</b>	<b>S</b>	<b>24</b>	
Model		Adapter Type		Port Density		
Model 09	<b>09</b>	SC	<b>SC</b>	24 Ports	<b>24</b>	
		LC	<b>LC</b>			

Example: **OTB09EMSCS24** - Unloaded SC Simplex 24 Port Outdoor Terminal Box Model 9

For any queries, please contact the Linxcom team using the details below.