



## COPPER STRUCTURED CABLING

# PATCH PANEL

# STP CAT6<sup>A</sup> IDC

### PRODUCT SPECIFICATIONS

Linxcom CAT 6<sup>A</sup> patch panels are 19- inch rack mountable.

All panels comply with the EIA/TIA stands for Category 6<sup>A</sup> and are available in 24 ports. UL 94V-0 Rated

Every patch panel is made with high quality materials and is tested and certified.



### APPLICATIONS

- LAN
- WAN

### FEATURES

- IDC Design
- 24 Port
- Powder Coated Finish

### BENEFITS

- Broadband/ Ethernet
- No Special Tools Required
- High Density

### CONSTRUCTION SPECIFICATIONS

U Size	1U	Insertion Force	900g
AWG Rating	22~26	Retention Strength	7.7kgs between Jack + Plug
Width	482.6mm	Jack Durability	750 Cycles
Depth	131mm	IDC Durability	Max 200 punching times
RJ45 Housing	Phosphor Bronze 50-60 micro-inch Nickel		

### ENVIRONMENTAL SPECIFICATIONS

Operation (°C)	-40~+70
Storage(°C)	-40~+70

### ORDERING INFORMATION

STP6AIDCPP24	1U CAT 6 <sup>A</sup> STP 24 Port Patch Panel
--------------	-----------------------------------------------



## COPPER STRUCTURED CABLING

# PATCH PANEL

# STP CAT6<sup>A</sup> IDC

### Technical Drawing

